





ISO 9001  
NO:954596



ISO 14001  
NO:771475



OHSAS 18001  
NO:K033008

## Specifications

MODEL		DK75	DK90
<b>ENGINE</b>			
Model		1104D-44T	1104D-44TT
Type		4Cyl., In-line Vertical, Water-Cooled	4Cyl., In-line Vertical, Water-Cooled
Engine Gross	HP(kw)	4-Cycle Turbo Diesel Engine 74.4(55.5)	4-Cycle Turbo Diesel Engine 91.2(68)
PTO	HP(kw)	60(44.6)	78(57)
Displacement	cu.in.(cc)	268.5(4400)	268.5(4400)
Rated Revolution	rpm	2200	2200
Fuel tank capacity	u.s.gal(ℓ )	33.0(125)	33.0(125)
<b>DRIVE TRAIN</b>			
Clutch		Dry Single Plate - Single Stage Type (Ceramic Type)	Dry Single Plate - Single Stage Type (Ceramic Type)
Transmission		Fully Synchronized Shuttle	Fully Synchronized Shuttle
Speeds		12F 12R	16F 16R
Differential Lock		Standard (Rear Only)	Standard (Rear Only)
Brake		Wet Disc (Hydraulic)	Wet Disc (Hydraulic)
PTO		Hydrostatic, Independent	Hydrostatic, Independent/Ground
Rear	rpm	540	540/1000
Mid	rpm	N/A	N/A
<b>HYDRAULIC SYSTEM</b>			
Pump		Gear(Tandem)	Gear(Tandem)
Pump Capacity (Max. Flow Rate)	gpm(ℓ /min)	1st : 12.8(48.4) 2nd : 9.3(35.2)	1st : 12.8(48.4) 2nd : 9.3(35.2)
3-Point Hitch		Cat. II	Cat. II
Maximum Lift Capacity (24" aft. of hitch)	lbs.(kg)	5290(2400)	5290(2400)
Hydraulic Lift Control System		Position, Draft, Mixed Control	Position, Draft, Mixed Control
Steering		Hydrostatic Power Steering	Hydrostatic Power Steering
<b>TIRE SIZE</b>			
Front Ag		11.2 x 24, 8PLY, Tubeless	12.4 x 24, 8PLY, Tubeless
Rear Ag		16.9 x 30, 8PLY, Bias Tube	18.4 x 34, 8PLY, Bias Tube
<b>TRAVELING SPEEDS</b>			
Front	mph(km/h)	1.09-19.37 (1st - 1.76, 12th - 31.18 )	0.16 ~ 21.57 (1st - 0.25, 16th - 34.72 )
Reverse	mph(km/h)	0.98-17.24 (1st - 1.57, 12th - 27.75 )	0.14 ~ 19.2 (1st - 0.22, 16th - 30.90 )
<b>DIMENSIONS</b>			
Overall Length (includes 3-pt hitch)	in.(mm)	162.2(4120)	162.2(4120)
Overall Width (minimum tread)	in.(mm)	77.8(1977)	78.7(2000)
Overall Height (from top of Cab)	in.(mm)	108.3(2750)	111.0(2820)
Wheelbase	in.(mm)	90. 7(2305)	90. 7(2305)
Min. Ground Clearance	in.(mm)	16.7(425)	19.5(495)
Tread	in.(mm)	59.7 ~ 67.6(1516-1716)	59.7 ~ 67.6(1516-1716)
	in.(mm)	61.6 ~ 77.5(1565-1968)	61.6 ~ 77.5(1565-1968)
Min. Turning Radius(with brake)	feet(mm)	12.8(3900)	12.8(3900)
Weight with Cab w/o Front Weights, w/Ag Tires	lbs.(kg)	7749(3515)	8905(4039)

Specifications and design are subject to change without notice.

## Standard Equipment

- Telescopic 3 Point Hitch Ends
- Telescopic Stabilizers
- Crank Adjustable Lift Link
- DK90-Creep Speed Gear
- Side Mount Hydraulic Couplers
- Single Lever Joystick For Loader Operation
- Hydrostatic Power Steering
- Rear Differential Lock
- Hydraulic Brakes
- Hand & Foot Throttles
- Adjustable Drawbar / Adjustable Seat
- Head Lights / Safety Lights
- Safety Start Switch
- Front & Rear Working Light
- Dual(DK90)/Single(DK75) Remote Hyd. Valves
- Single Element Air Cleaner
- DK90-Ground PTO
- Tilt Steering Wheel
- Oil Cooler
- 4WD, Push Button Engaged for Easier Operation
- Flip-up PTO Guard
- DK90-AM/FM Radio CD Player(w/ iPod cable for MP3)
- DK90-Rear Window Defogger
- Power Outlet(3P) and 7 Pole Socket
- Front Wiper
- DK90-Rear Wiper

## Optional Equipment

- DK90-3rd Remote Hydraulic Valve (Detent Floating Valve)
- DK75-2nd,3rd Remote Hydraulic Valve (Detent Floating Valve)
- Rear Sub Cylinder
- Front End Weights
- DK75-AM/FM Radio CD Player (w/ iPod cable for MP3)
- DK75-Rear Wiper
- Cooler

## Available KIOTI Attachments

- DK90&75-Front End Loader (Self Leveling , Quick Attach)
- Contact your local KIOTI dealer for available implements and attachments



KIOTI Tractor Division  
DAEDONG - USA, INC.  
6300 KIOTI Drive, Wendell, NC 27591  
toll free 877-GO-KIOTI • fax 919-374-5001  
web www.KIOTI.com

Dealer Imprint Area

Part Number LIT-DK75/90-1

**DK75/DK90**


**KIOTI UTILITY TRACTOR**



  
**KIOTI**<sup>®</sup>  
*run ahead of the pack*

# Exceptional quality and dependability in the DK series tractors

Keeps you *ahead of the pack*




## Rear PTO

A 540 PTO is standard on the DK 75. A 540 PTO and 1,000 PTO are both standard on the DK 90. Changing speeds is as simple as shifting a lever. A ground speed PTO is available on the DK 90 for those special applications requiring precise travel speed.



## Auto PTO

A unique feature to the Kioti DK Series tractors is Auto PTO. When selected, the Auto PTO will “automatically” engage the PTO when the three point hitch is lowered and “automatically” disengage the PTO when raised. This feature reduces noise and vibration associated with PTO driven implements that are frequently raised and lowered.



## Remote Hydraulic Valves

The DK 75 comes standard with a single remote valve and the DK 90 comes standard with dual remote valves to accommodate a wide variety of attachments and implements. A second remote valve is an available option for the DK 75 and a third remote valve is an available option for both the DK 75 and DK 90.



### Deluxe Cabin

The deluxe cab comes standard with all the comforts of home including: front wipers, a/c and heat, auxiliary power outlet, rearview mirror, jacket hanger, ashtray and sunroof. In addition, the ergonomically designed work station places operator controls within easy reach of the deluxe suspension seat to minimize fatigue for those long days in the field. Rear wipers and AM/FM/CD radio with IPOD connection are available options on the DK 75 but comes standard on the DK 90.



### Single Lever Joystick

Mid mount hydraulics and a single lever joystick for loader operations are standard on the DK 75 and the DK 90.



### Power Steering

Equipped with hydrostatic power steering, the DK 75 and the DK 90 have smooth, responsive steering that requires minimal operator effort regardless of the task at hand.





DK Series DK series high-performance tractors pack impressive power and smooth handling into one dependable workhorse. With many standard features that are options with the competition and an operator friendly cab, the DK 75 and the DK 90 are ready for any job that demands a durable tractor.



**Convenient Hood**

The streamlined, one piece hood accompanied by a vertical exhaust adjacent to the cab post offers great forward visibility even when equipped with a loader. With a quick release latch and removable engine panels, the DK 75 and the DK 90 are easy to maintain and service.



**Fuel Tank**

With a 33 gallon fuel tank and a fuel efficient engine, the DK 75 and the DK 90 are able to work a long time between fuel breaks. A large filler neck with a wide spout is conveniently located next to the left cab steps to make re-fueling quick and easy.



**Deluxe Seat**

A fully adjustable, suspension seat allows the operator to ride in comfort no matter what the job may be. A retractable seatbelt is standard on all Kioti tractors to ensure operator safety.



**Telescopic CAT II Hitch**

Category II 3-point hitch with standard telescopic link ends make attaching implements quicker and easier than fixed links and enhances operator safety. The DK 75 and the DK 90 come standard with telescopic stabilizers and a RH leveling box to provide operator's with a wide ranges of customizable 3-point hitch options depending on the job at hand.



**Transmission**

The DK 90 with 16 forward and reverse gears have travel speeds to match any task around the farm. The DK 75 has 12 forward and reverse gears making it very versatile and adaptable to your applications. The fully synchronized shuttle simplify loader work. The DK 90 also has a factory installed creeper gear that propels the tractor at speeds as low as .12 MPH.